

12 ch ECG



Interpretive 12 Channel Resting  
ECG with Large LCD Touch Screen

# CardioTouch 3000

- \* Convenient A4 size print-outs allow for easy chart filing
- \* Grid function allows you to use low cost plain fax paper
- \* One-touch operation (monitoring, recording mode)
- \* 12Ch simultaneous display
- \* 320 x 240 LCD
- \* Touch screen for easy operation
- \* LCD Brightness Control
- \* Rotary Key Access to All Menus

- 12channel interpretive ECG
- Over 130 kinds of interpretation results based on advanced Minnesota code
- Memory for up to 30 patients
- Real-time preview monitor
- PC compatible through LAN
- Multi-language(English,Russian,French, German,Italian,Chinese,Spanish)available
- Lead fault message
- Pace maker detection



# SPECIFICATIONS

## ECG >>>

<b>ECG leads</b>	10 lead, 12 channel simultaneous ECG and acquisition
<b>Dimension</b>	296(W) × 305.5(H) × 92.5(D)mm, approx.3.5kg
<b>Recording channel</b>	3 channels, 6 channels, 12 channels, 60 second 1 channel and beat report
<b>Sensitivity</b>	2.5, 5, 10, 20, auto(I-aVF: 10, V1-V6: 5) mm/mV
<b>Printing speed</b>	12.5, 25, 50 mm/s
<b>Sampling rate</b>	500 samples/sec
<b>Filters</b>	AC(50/60 Hz, -20dB or better) Muscle(25-35 Hz, -3dB or better) Base line drift(0.1 Hz, -3dB or better) Low pass filter : off, 40 Hz, 100 Hz, 150 Hz
<b>Display</b>	320 × 240 graphic LCD display, 3 and 12 channels preview
<b>Monitor display</b>	ID, date, sensitivity, speed, filter, form, rhythm lead
<b>User interface</b>	Touch screen(Alphanumeric and symbol available), Keyboard, rotary push-knob(pop-up menu)
<b>Patient data</b>	ID, name, age, sex, height, weight, smoke, race
<b>Basic measurement</b>	Heart rate, PR int, QRS dur, QT/QTc, P-R-T axis
<b>Recorder</b>	Thermal print head, roll paper Report papers : width : A4 : 210mm or 8.5" / length : A4 : 300mm or 11" Resolution : vertical : 8dot/mm / horizontal : 16dot/mm
<b>Electrical</b>	Internal noise: 20μV (p-p)max / Input circuit : floating input Input impedance : ≥ 10M Ω / Input voltage range : ≥ ± 5mV Common mode rejection : > 100dB / DC offset voltage : ≥ ± 300mV Time constant : 3.2sec / Patient leakage current : < 10μA Frequency response : 0.05 ~ 150 Hz / Isolated and defibrillation protected
<b>Signal quality control</b>	Disconnected lead detection, Pacemaker pulse detection
<b>ECG data storage</b>	storage for 30 ECGs (Internal on flash memory)
<b>Power</b>	Power supply : AC or built-in battery(option) 95 ~ 240 VAC, 50/60 Hz, 1.0 ~ 0.5A, 60W max
<b>Battery(Ni-MH)</b>	1 hour of normal use (approx. 100 ECG printouts)
<b>Communication</b>	PC connection with RS232 interface and LAN
<b>Safety conformity</b>	Class I, Type BF, CE, CSA, FDA, KFDA, SFDA, CCC
<b>Environment</b>	Operating humidity : 30-85% / Operating temperature : 10 ~ 40℃ Atmospheric pressure : 70 ~ 106KPa
<b>Standard accessory</b>	Power cord 1 EA, Patient cable 1 EA, Limb 1 set(4 EA), Chest ball 1 set(6 EA), Chart paper 1 EA, Operation manual 1 EA
<b>Options</b>	Rechargeable battery, Cart, Hanger, Bag, PC S/W

\* Specifications can be changed without prior notification.



**Main office : Bionet Co., Ltd.**  
Tel : +82-2-6300-6418(Int'l)  
e-mail : sales@ebionet.com(Int'l)

**North America : Bionet America, Inc.**  
Tel : +1-714-734-1760

**Europe : MGB Endoskopische Ger-te GmbH Berlin**  
Tel : +49-30-6392-7010

**China : Bionet China**  
Tel : +86-10-58220564

**www.ebionet.com**  
+82-2-6300-6477(Domestic)  
yunms@ebionet.com(Domestic)

**www.bionetus.com**  
e-mail : sales@bionetus.com

**www.mgb-berlin.de**  
e-mail : info@mgb-berlin.de

e-mail : sales-china@ebionet.com